

Frequency Allocation Summary

From the Airborne (U) equipment we will transmit

10.71 Mb/s, $\frac{1}{2}$ FEC, clear O-QPSK - designated in 1494 as 21M4G1D

It must be in the 14.4 GHz – 14.83 GHz range, on a 5 MHz increment

From the Surface (N) equipment we will transmit

2 Mb/s, $\frac{1}{2}$ FEC, clear BPSK - designated in 1494 as 8M00G1D

It must be in the 15.150 GHz – 15.350 GHz range, on a 5 MHz increment

Surface (N) 1494

NTIA GENERAL INFORMATION

1. APPLICATION TITLE (U) L-3 Wideband Data Link (CWDL)		
2. SYSTEM NOMENCLATURE (U) Wideband Data Link (CWDL)		
3. STAGE OF ALLOCATION (U) <input type="checkbox"/> a. STAGE 1 CONCEPTUAL <input type="checkbox"/> b. STAGE 2 EXPERIMENTAL <input type="checkbox"/> c. STAGE 3 DEVELOPMENTAL <input type="checkbox"/> d. STAGE 4 OPERATIONAL		
4. FREQUENCY REQUIREMENTS		
a. FREQUENCY(IES) (U) 14.400 GHz - 14.830 GHz 15.150 GHz - 15.350 GHz [REDACTED] [REDACTED]		
b. EMISSION DESIGNATORS (U) [REDACTED] 8M00G1D 21M4G1D [REDACTED] See Data Overflow Page		
5. PURPOSE OF SYSTEM, OPERATIONAL AND SYSTEM CONCEPTS (U) The Wideband Data Links provide near-real-time C3 and wideband sensor discrimination capabilities between airborne platforms and surface terminals at programmable rates. (WARTIME USE) <input type="checkbox"/> a. YES <input type="checkbox"/> b. NO		
6. INFORMATION TRANSFER REQUIREMENTS (U) [REDACTED]		
7. ESTIMATED INITIAL COST OF THE SYSTEM [REDACTED]		
8. TARGET DATE FOR		
a. APPLICATION APPROVAL [REDACTED]	b. SYSTEM ACTIVATION [REDACTED]	c. SYSTEM TERMINATION [REDACTED]
9. SYSTEM RELATIONSHIP AND ESSENTIALITY (U) Related/Similar systems: Guardrail J/F 12/6534, Common High Bandwidth Data Link - Shipboard Terminal (CHBDL-ST), Modular Interoperable Data Link (MIST) J/F 12/6649, ATARS J/F 12/6562, Real Time Sensor Data Link (RTSDL)		
10. REPLACEMENT INFORMATION (U) [REDACTED]		
11. RELATED ANALYSIS AND/OR TEST DATA (U) [REDACTED]		
12. NUMBER OF MOBILE UNITS (U) [REDACTED]		
13. GEOGRAPHICAL AREA FOR		
a. STAGE 2 (U) NA		
b. STAGE 3 (U) [REDACTED]		
c. STAGE 4 (U) [REDACTED]		
14. LINE DIAGRAM (U) See Page(s)		15. SPACE SYSTEMS (U) See Page(s) NA
16. TYPE OF SERVICE(S) FOR STAGE 4 (U) [REDACTED]		17. STATION CLASS(ES) FOR STAGE 4 (U) FA
18. REMARKS () [REDACTED]		
DOWNGRADING INSTRUCTIONS		SIN/
		CLASSIFICATION UNCLASSIFIED

TRANSMITTER EQUIPMENT CHARACTERISTICS

1. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) Wideband Data Link (CWDL) Surface Transmitter	2. MANUFACTURER'S NAME (U) L-3 Communications
3. TRANSMITTER INSTALLATION (U) Ground Locations	4. TRANSMITTER TYPE (U) BPSK, <i>Communications</i>
5. TUNING RANGE (U) 15.150 GHz - 15.350 GHz	6. METHOD OF TUNING (U) Crystal Controlled PLL Synthesizer
7. RF CHANNELING CAPABILITY (U) 15.15, 5MHz increments	8. EMISSION DESIGNATORS (U) <i>[redacted]</i> (U) 8M00G1D (U) <i>[redacted]</i> See Data Overflow Page
9. FREQUENCY TOLERANCE (U) 0.03 ppm	12. EMISSION BANDWIDTH See Data Overflow Page <input checked="" type="checkbox"/> CALCULATED <input type="checkbox"/> MEASURED
10. FILTER EMPLOYED (U) <input checked="" type="checkbox"/> a. YES <input type="checkbox"/> b. NO	a. -3 dB (U) <i>[redacted]</i> (U) 3.49 MHz (U) <i>[redacted]</i>
11. SPREAD SPECTRUM (U) <input type="checkbox"/> a. YES <input checked="" type="checkbox"/> b. NO	b. -20 dB (U) <i>[redacted]</i> (U) 21.16 MHz (U) <i>[redacted]</i>
13. MAXIMUM BIT RATE (U) <i>2 Mb/s</i>	c. -40 dB (U) <i>[redacted]</i> (U) NA (U) <i>[redacted]</i>
14. MODULATION TECHNIQUES AND CODING (U) See Remarks	d. -60 dB (U) <i>[redacted]</i> (U) 68.6 MHz (U) <i>[redacted]</i>
16. PRE-EMPHASIS (U) <input type="checkbox"/> a. YES <input checked="" type="checkbox"/> b. NO	e. OC-BW (U) <i>[redacted]</i> (U) 23.86 MHz (U) <i>[redacted]</i>
19. POWER See Data Overflow Page	15. MAXIMUM MODULATION FREQUENCY (U) <i>NA</i>
a. MEAN (U) <i>2W</i> (U) <i>[redacted]</i> (U) <i>[redacted]</i>	17. DEVIATION RATIO (U) NA
b. PEP (U) NA (U) NA (U) <i>NA</i>	18. PULSE CHARACTERISTICS See Data Overflow Page
20. OUTPUT DEVICE (U) Solid State Power Amplifier	a. RATE (U) NA (U) NA (U) NA
22. SPURIOUS LEVEL (U) -80 dB	b. WIDTH (U) NA (U) NA (U) NA
23. FCC TYPE ACCEPTANCE NO. (U) NA	c. RISE TIME (U) NA (U) NA (U) NA
24. REMARKS (U)	d. FALL TIME (U) NA (U) NA (U) NA
7. 15.15 GHz, 5 MHz increments	e. COMP RATIO (U) NA (U) NA (U) NA
10. 12-section waveguide filter	21. HARMONIC LEVEL
13. Includes R = 1/2 Convolutional Encoding FEC	a. 2nd (U) -65 dB
14. <i>8M00G1D: 2Mb/s, R=1/2 FEC, CLEAR BPSK</i>	b. 3rd (U) -65 dB
	c. OTHER (U) -80 dB

24. REMARKS (U)

7. 15.15 GHz, 5 MHz increments

10. 12-section waveguide filter

13. Includes R = 1/2 Convolutional Encoding FEC

14. *8M00G1D: 2Mb/s, R=1/2 FEC, CLEAR BPSK*

RECEIVER EQUIPMENT CHARACTERISTICS

1. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) Wideband Data Link (CWDL) - Surface Receiver				2. MANUFACTURER'S NAME (U) L-3 Communications			
3. RECEIVER INSTALLATION (U) Ground /				4. RECEIVER TYPE (U) Single Conversion Superheterodyne			
5. TUNING RANGE (U) 14.400 GHz - 14.830 GHz				6. METHOD OF TUNING (U) Crystal Controlled PLL Synthesizer			
7. RF CHANNELING CAPABILITY (U) G14.4 5MHz Increments				8. EMISSION DESIGNATORS 21M4G1D (U) See Data Overflow Page			
9. FREQUENCY TOLERANCE (U) 10 ppm				11. RF SELECTIVITY <input checked="" type="checkbox"/> CALCULATED <input type="checkbox"/> MEASURED			
10. IF SELECTIVITY		1st (U)	2nd (U)	3rd (U)	a. -3 dB (U) 570 MHz		
a. -3 dB	36.5 MHz	NA	NA	b. -20 dB (U) 607 MHz			
b. -20 dB	59.1 MHz	NA	NA	c. -60 dB (U) 725 MHz			
c. -60 dB	103.7 MHz	NA	NA	d. Preselection Type (U) Waveguide Filter			
12. IF FREQUENCY				13. MAXIMUM POST DETECTION FREQUENCY (U) NA			
a. 1st (U) 680 MHz				14. MINIMUM POST DETECTION FREQUENCY (U) NA			
b. 2nd (U) NA				16. MAXIMUM BIT RATE (U) 10.71 Mb/s			
c. 3rd (U) NA				17. SENSITIVITY			
15. OSCILLATOR TUNED		1st (U)	2nd (U)	3rd (U)	a. SENSITIVITY (U) -91 dBm		
a. ABOVE TUNED FREQUENCY					b. CRITERIA (U) BER = 10E-6		
b. BELOW TUNED FREQUENCY					c. NOISE FIG (U) 3.5 dB		
c. EITHER ABOVE OR BELOW THE FREQUENCY		X			d. NOISE TEMP (U) NA		
18. DE-EMPHASIS (U) <input type="checkbox"/> a. YES <input checked="" type="checkbox"/> b. NO				20. SPURIOUS REJECTION (U) 85 dB			
19. IMAGE REJECTION (U) 85 dB				21. REMARKS (U) 7. 14.4 GHz, 5 MHz increments			

ANTENNA EQUIPMENT CHARACTERISTICS

1. (U) <input type="checkbox"/> a. TRANSMITTING		<input type="checkbox"/> b. RECEIVING		<input checked="" type="checkbox"/> c. TRANSMITTING AND RECEIVING	
2. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) TC DL-N 36" Surface Antenna			3. MANUFACTURER'S NAME (U) L-3 Communications		
4. FREQUENCY RANGE (U) 14400 MHz - 15350 MHz			5. TYPE (U) Parabolic Reflector		
6. POLARIZATION (U) Right-Hand Circular			7. SCAN CHARACTERISTICS		
8. GAIN			a. TYPE (U) MECHANICAL SCAN		
a. MAIN BEAM (U) 40 dBi			b. VERTICAL SCAN (U) Mechanical		
b. 1st MAJOR SIDE LOBE (U) 12 dBi @ 2.5 deg			(1) Max Elev (U) +85 deg		
9. BEAMWIDTH			(2) Min Elev (U) -5 deg		
a. HORIZONTAL (U) 1.7 deg			(3) Scan Rate (U) 10 degrees/second		
b. VERTICAL (U) 1.7 deg			c. HORIZONTAL SCAN (U) Mechanical		
10. REMARKS (U)			(1) Sector Scanned (U) 0-360 degrees		
			(2) Scan Rate (U) 10 degrees/second		
			d. SECTOR BLANKING (U) <input type="checkbox"/> (1) YES <input checked="" type="checkbox"/> (2) NO		

4. Frequencies in MHz (14.40 GHz - 15.35 GHz)

8b. 12 dBi (elevation) @ 2.5 deg.
21 dBi (azimuth) @ 2.3 deg.

ANTENNA EQUIPMENT CHARACTERISTICS

1. (U) a. TRANSMITTING b. RECEIVING c. TRANSMITTING AND RECEIVING

2. NOMENCLATURE, MANUFACTURER'S MODEL NO.

(U) *Single* Band Surface Omni Antenna

3. MANUFACTURER'S NAME

(U) L-3 Communications

5. TYPE (U) Dipole

4. FREQUENCY RANGE

(U) *14.4* GHz - 15.350 GHz

7. SCAN CHARACTERISTICS

a. TYPE (U) NA

6. POLARIZATION

(U) Right-Hand Circular

b. VERTICAL SCAN (U) NA

(1) Max Elev (U) NA

8. GAIN

(2) Min Elev (U) NA

(3) Scan Rate (U) NA

a. MAIN BEAM

(U) 3 dBi

c. HORIZONTAL SCAN (U) NA

(1) Sector Scanned (U) NA

(2) Scan Rate (U) NA

b. 1st MAJOR SIDE LOBE

(U) -2.5 dBi @ 40 deg

d. SECTOR BLANKING (U) (1) YES (2) NO

9. BEAMWIDTH

a. HORIZONTAL

(U) 360 deg

b. VERTICAL

(U) 36 deg

10. REMARKS (U)

[REDACTED]

GENERAL CONTINUATION PAGE

The Wideband Data Link (CWDL) is a secure, digital wideband data link intended to provide connectivity between aircraft and surface platforms at data rates from 200 kb/s to 45 Mb/s. Interfaces for user network data (Ethernet), Video, and Acoustic sensor data are provided to provide a near-real-time transmission of user or sensor data between airborne and surface platforms.

Airborne (U) 1494

APPLICATION FOR EQUIPMENT FREQUENCY ALLOCATION	CLASSIFICATION UNCLASSIFIED	DATE [REDACTED]	J/F 12/
			Page 1 of 16 Pages

DOD GENERAL INFORMATION

TO [REDACTED]	FROM [REDACTED]
------------------	--------------------

1. APPLICATION TITLE (U) Tactical Common Data Link (TCDL)

2. SYSTEM NOMENCLATURE (U) Tactical Common Data Link (TCDL)

3. STAGE OF ALLOCATION (U) a. STAGE 1 CONCEPTUAL b. STAGE 2 EXPERIMENTAL c. STAGE 3 DEVELOPMENTAL d. STAGE 4 OPERATIONAL

4. FREQUENCY REQUIREMENTS
a. FREQUENCY(IES) (U) 15.15 GHz - 15.35 GHz 14.40 GHz - 14.83 GHz
b. EMISSION DESIGNATORS (U) 8M00G1D 21M4G1D
See Data Overflow Page

5. TARGET STARTING DATE FOR SUBSEQUENT STAGES
a. STAGE 2 (U) NA b. STAGE 3 (U) NA c. STAGE 4 (U) 01-01-00

6. EXTENT OF USE (U)

7. GEOGRAPHICAL AREA FOR

a. STAGE 2 (U) NA

b. STAGE 3 (U)

c. STAGE 4 (U)

8. NUMBER OF UNITS

a. STAGE 2 b. STAGE 3 c. STAGE 4

9. NUMBER OF UNITS OPERATING SIMULTANEOUSLY IN THE SAME ENVIRONMENT(U)

10. OTHER J/F 12 APPLICATION NUMBER(S) TO BE (U)
 a. SUPERSEDED J/F 12/
 b. RELATED J/F 12/ [REDACTED]

11. IS THERE ANY OPERATIONAL REQUIREMENT AS DESCRIBED IN THE INSTRUCTIONS FOR PARAGRAPH 11?
(U) a. YES b. NO c. NAVAIL

12. NAMES AND TELEPHONE NUMBERS (U)

a. PROGRAM MANAGER	(1) COMMERCIAL [REDACTED]	(2) DSN [REDACTED]
b. PROJECT ENGINEER	(1) COMMERCIAL [REDACTED]	(2) DSN [REDACTED]

13. REMARKS (U)

Block 11: Operates with Army's AN/UPQ-3 (A/B) [J/F 12/ 6534] and Navy's Common High Bandwidth Data Link - Shipboard Terminal (CHBDL-ST) AN/USQ-123(V). Also operates with Modular Interoperable Surface Terminal (MIST) [J/F 12/ 6649].

DOWNGRADING INSTRUCTIONS

J/F 12/

CLASSIFICATION
UNCLASSIFIED

TRANSMITTER EQUIPMENT CHARACTERISTICS

1. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) Tactical Common Data Link (TCDL) - Airborne Transmitter		2. MANUFACTURER'S NAME (U) L-3 Communications	
3. TRANSMITTER INSTALLATION (U) Aircraft Platform		4. TRANSMITTER TYPE (U) QPSK, Communications	
5. TUNING RANGE (U) 14.40 GHz - 14.83 GHz		6. METHOD OF TUNING (U) Crystal Controlled Synthesizer	
7. RF CHANNELING CAPABILITY (U) 14.4GHz, 5MHz increments, 87 channels		8. EMISSION DESIGNATORS (U) (U) 21M4G1D (U) See Data Overflow Page	
9. FREQUENCY TOLERANCE (U) 0.03 ppm		12. EMISSION BANDWIDTH See Data Overflow Page <input checked="" type="checkbox"/> CALCULATED <input type="checkbox"/> MEASURED	
10. FILTER EMPLOYED (U) <input checked="" type="checkbox"/> a. YES <input type="checkbox"/> b. NO		a. -3 dB (U) (U) 9.4 MHz (U)	
11. SPREAD SPECTRUM (U) <input type="checkbox"/> a. YES <input checked="" type="checkbox"/> b. NO		b. -20 dB (U) (U) 57.4 MHz (U)	
13. MAXIMUM BIT RATE (U) 10.71 Mbps		c. -40 dB (U) (U) NA (U)	
14. MODULATION TECHNIQUES AND CODING (U) Rate 1/2 convolutional coding, constraint length 7. 1D is a DSSS waveform.		d. -60 dB (U) (U) 228 MHz (U)	
16. PRE-EMPHASIS (U) <input type="checkbox"/> a. YES <input checked="" type="checkbox"/> b. NO		e. OC-BW(U) (U) 63 MHz (U)	
19. POWER See Data Overflow Page a. MEAN (U) 2 W (U) (U)		15. MAXIMUM MODULATION FREQUENCY (U) NA	
b. PEP (U) NA (U) NA (U) NA		17. DEVIATION RATIO (U) NA	
20. OUTPUT DEVICE (U) Solid State Power Amplifier (SSPA)		18. PULSE CHARACTERISTICS See Data Overflow Page a. RATE (U) NA (U) NA (U) NA	
22. SPURIOUS LEVEL (U) -80 dB		b. WIDTH (U) NA (U) NA (U) NA	
23. FCC TYPE ACCEPTANCE NO. (U) NA		c. RISE TIME (U) NA (U) NA (U) NA	
		d. FALL TIME (U) NA (U) NA (U) NA	
		e. COMP RATIO (U) NA (U) NA (U) NA	
		21. HARMONIC LEVEL	
		a. 2nd (U) -65 dB	
		b. 3rd (U) -65 dB	
		c. OTHER (U) -80 dB	

24. REMARKS (U) Block 10: Emission is controlled by two filters. The first filter is a 3-pole Chebyshev IF filter centered @ 680 MHz, with a 90 MHz 3 dB bandwidth. It provides 40 dB minimum stopband attenuation. The second filter is an RF waveguide filter with a 3 dB bandwidth of 430 MHz. The wideband RF filtering provides 80 dB minimum stopband attenuation at 14.15 GHz and below and 105 dB minimum attenuation at 15.15 GHz and above.

Block 14: [REDACTED]
21M4G1D: 10.71 Mb/s, R=1/2 FEC, clear O-QPSK

[REDACTED]

[REDACTED]

[REDACTED]

RECEIVER EQUIPMENT CHARACTERISTICS

1. NOMENCLATURE, MANUFACTURER'S MODEL NO. (U) Tactical Common Data Link (TCDL) - Airborne Receiver				2. MANUFACTURER'S NAME (U) L-3 Communications			
3. RECEIVER INSTALLATION (U) Aircraft Platform				4. RECEIVER TYPE (U) Dual Conversion Superheterodyne			
5. TUNING RANGE (U) 15.15 GHz - 15.35 GHz				6. METHOD OF TUNING (U) Crystal Controlled Synthesizer			
7. RF CHANNELING CAPABILITY (U) 15.15GHz, 5MHz increments, 41 channels				8. EMISSION DESIGNATORS (U) 8MφφG1D See Data Overflow Page			
9. FREQUENCY TOLERANCE (U) 10 ppm				11. RF SELECTIVITY <input checked="" type="checkbox"/> CALCULATED <input type="checkbox"/> MEASURED			
10. IF SELECTIVITY		1st (U)	2nd (U)	3rd (U)	a. -3 dB (U) 200 MHz		
a. -3 dB	200 MHz	120 MHz	NA	b. -20 dB (U) 410 MHz			
b. -20 dB	450 MHz	149 MHz	NA	c. -60 dB (U) 560 MHz			
c. -60 dB	1.5 GHz	278 MHz	NA	d. Preselection Type (U) Waveguide Filter			
12. IF FREQUENCY				13. MAXIMUM POST DETECTION FREQUENCY (U) NA			
a. 1st (U) 2935 MHz				14. MINIMUM POST DETECTION FREQUENCY (U) NA			
b. 2nd (U) 680 MHz				16. MAXIMUM BIT RATE (U) 2 Mb/s			
c. 3rd (U) NA				17. SENSITIVITY			
15. OSCILLATOR TUNED		1st (U)	2nd (U)	3rd (U)	a. SENSITIVITY (U) -98 dBm		
a. ABOVE TUNED FREQUENCY					b. CRITERIA (U) BER 10E-6		
b. BELOW TUNED FREQUENCY		X	X		c. NOISE FIG (U) 3.5 dB		
c. EITHER ABOVE OR BELOW THE FREQUENCY					d. NOISE TEMP (U) NA		
18. DE-EMPHASIS (U) <input type="checkbox"/> a. YES <input checked="" type="checkbox"/> b. NO				20. SPURIOUS REJECTION (U) 85 dB			
19. IMAGE REJECTION (U) 85 dB				21. REMARKS (U)			

ANTENNA EQUIPMENT CHARACTERISTICS

1. (U) a. TRANSMITTING b. RECEIVING c. TRANSMITTING AND RECEIVING

2. NOMENCLATURE, MANUFACTURER'S MODEL NO.
(U) TCDL AIRBORNE ONMI ANTENNA

3. MANUFACTURER'S NAME
(U) L-3 Communications

5. TYPE (U) Bicone

4. FREQUENCY RANGE
(U) 14.40 GHz - 14.83 GHz

7. SCAN CHARACTERISTICS

a. TYPE (U) FIXED

6. POLARIZATION
(U) Right-Hand Circular

b. VERTICAL SCAN (U) NA

(1) Max Elev (U) NA

(2) Min Elev (U) NA

8. GAIN

(3) Scan Rate (U) NA

a. MAIN BEAM
(U) 3.0 dBi

c. HORIZONTAL SCAN (U) NA

b. 1st MAJOR SIDE LOBE
(U)

(1) Sector Scanned (U) NA

9. BEAMWIDTH

(2) Scan Rate (U) NA

a. HORIZONTAL
(U) 360 deg

b. VERTICAL
(U) 42 deg

d. SECTOR BLANKING (U) (1) YES (2) NO

10. REMARKS (U)

NTIA GENERAL INFORMATION

1. APPLICATION TITLE (U) Tactical Common Data Link (TCDL)

2. SYSTEM NOMENCLATURE (U) Tactical Common Data Link (TCDL)

3. STAGE OF ALLOCATION (U) a. STAGE 1 CONCEPTUAL b. STAGE 2 EXPERIMENTAL c. STAGE 3 DEVELOPMENTAL d. STAGE 4 OPERATIONAL

4. FREQUENCY REQUIREMENTS
 a. FREQUENCY(IES) (U) 14.40 GHz - 14.83 GHz 15.15 GHz - 15.35 GHz
 b. EMISSION DESIGNATORS (U) [REDACTED] 8M00G1D 21M4G1D
See Data Overflow Page

5. PURPOSE OF SYSTEM, OPERATIONAL AND SYSTEM CONCEPTS (WARTIME USE) a. YES b. NO
 (U) The Tactical Common Data Link is a family of data links that provide C3 capabilities and connectivity between airborne platforms and surface terminals. It performs full duplex transfer of digital data between platforms at programmable rates.

6. INFORMATION TRANSFER REQUIREMENTS (U) [REDACTED]

7. ESTIMATED INITIAL COST OF THE SYSTEM (U) [REDACTED]

8. TARGET DATE FOR

a. APPLICATION APPROVAL (U)	b. SYSTEM ACTIVATION	c. SYSTEM TERMINATION
-----------------------------	----------------------	-----------------------

9. SYSTEM RELATIONSHIP AND ESSENTIALITY (U) Related/Similar systems: Guardrail J/F 12/ 6534, Common High Bandwidth Data Link - Shipboard Terminal (CHBDL-ST), Modular Interoperable Data Link (MIST) J/F 12/ 6649, and ATARS J/F 12/ 6562

10. REPLACEMENT INFORMATION (U) None

11. RELATED ANALYSIS AND/OR TEST DATA (U) None

12. NUMBER OF MOBILE UNITS (U) [REDACTED]

13. GEOGRAPHICAL AREA FOR

a. STAGE 2 (U) NA

b. STAGE 3 (U) [REDACTED]

c. STAGE 4 (U) [REDACTED]

14. LINE DIAGRAM (U) See Page(s) 18

15. SPACE SYSTEMS (U) See Page(s)

16. TYPE OF SERVICE(S) FOR STAGE 4 (U) [REDACTED]

17. STATION CLASS(ES) FOR STAGE 4 (U) MO MOD MOE

18. REMARKS (U)